

Safety Data Sheet

Copyright, 2018, Meguiar's, Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising Meguiar's, Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's, Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 37-4924-9 **Version number:** 2.00

Revision date: 04/07/2018 **Supersedes date:** 20/12/2017

Transportation version number: 1.00 (20/12/2017)

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

D166, Ultra Polishing Wax (26-123A): D16616, D16601

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive.

1.3. Details of the supplier of the safety data sheet

Address: Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF

Telephone: +44 (0)870 241 6696 E Mail: info@meguiars.co.uk Website: www.meguiars.co.uk

1.4. Emergency telephone number

+44 (0)870 241 6696

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

CLASSIFICATION:

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

HAZARD STATEMENTS:

H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international

regulations.

SUPPLEMENTAL INFORMATION

Supplemental Hazard Statements:

EUH208 Contains Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-

isothiazol-3-one. May produce an allergic reaction.

1% of the mixture consists of components of unknown acute oral toxicity.

Contains 1% of components with unknown hazards to the aquatic environment.

Information required per Regulation (EU) No 528/2012 on Biocidal Products:

Contains a biocidal product: Contains C(M)IT/MIT (3:1). May produce an allergic reaction.

Notes on labelling

H304 is not required on the label due to the product's viscosity Nota P applied to CASRN 64741-65-7.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Non-Hazardous Ingredients	Mixture			50 - 70	Substance not classified as hazardous
C10-13-iso-Alkanes	64742-48-9	265-150-3		10 - 30	Asp. Tox. 1, H304 - Nota P Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics		920-901-0		10 - 30	Asp. Tox. 1, H304; EUH066
Calcined Kaolin	92704-41-1	296-473-8		3 - 7	Substance not classified as hazardous
Poly(Dimethylsiloxane)	63148-62-9			3 - 7	Substance not classified as hazardous
C10-13-iso-Alkanes	64742-47-8	265-149-8		3 - 7	Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Flam. Liq. 3, H226; Skin Irrit. 2, H315; STOT SE 3, H336
Aluminium oxide	1344-28-1	215-691-6		1 - 5	Substance with a Community level exposure limit in the workplace
Silicic acid, sodium salt, reaction products with chlorotrimethylsilane	68988-56-7	273-530-5		0.5 - 1.5	Substance not classified as hazardous

and iso-Pr alc				
Heavy Alkylate Naphtha (Petroleum)	64741-65-7	265-067-2	< 0.5	Asp. Tox. 1, H304 - Nota P Aquatic Chronic 2, H411 Flam. Liq. 3, H226; STOT SE 3, H336; EUH066
Titanium dioxide	13463-67-7	236-675-5	< 0.3	Substance with a Community level exposure limit in the workplace
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9		< 0.0015	Acute Tox. 3, H331; Acute Tox. 3, H311; Acute Tox. 3, H301; Skin Corr. 1B, H314; Skin Sens. 1A, H317; Aquatic Acute 1, H400,M=1; Aquatic Chronic 1, H410,M=1

Note: Any entry in the EC# column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance Condition

Formaldehyde Carbon monoxide. Carbon dioxide. During combustion. During combustion. During combustion.

5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient CAS Nbr Agency Limit type Additional comments

Aluminium oxide 1344-28-1 UK HSC TWA(as inhalable dust):10

D166, Ultra Polishing Wax (26-123A): D16616, D16601

mg/m³;TWA(as respirable

dust):4 mg/m3

13463-67-7 UK HSC TWA(Inhalable):10

mg/m3;TWA(respirable):4

 mg/m^3

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

Titanium dioxide

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 166

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

MaterialThickness (mm)Breakthrough TimeNitrile rubber.No data availableNo data available

Applicable Norms/Standards Use gloves tested to EN 374

Respiratory protection

Wear respiratory protection if ventilation is inadequate to prevent overexposure. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure: Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid.

Appearance/Odour Yellow liquid with sweet citrus odor

Odour threshold *No data available.*

pH 7.9 - 8.5 Boiling point/boiling range 100 °C

Melting pointNot applicable.Flammability (solid, gas)Not applicable.Explosive propertiesNot classifiedOxidising propertiesNot classified

Flash point >= 93.3 °C [Test Method: Pensky-Martens Closed Cup]

[Details:D93-90]

Flash point > 93 °C (200 °F)

Autoignition temperatureNo data available.Flammable Limits(LEL)No data available.Flammable Limits(UEL)No data available.Vapour pressureNo data available.

Relative density 0.92 - 0.965 [*Ref Std*:WATER=1]

Water solubility Moderate

Solubility- non-waterNo data available.Partition coefficient: n-octanol/waterNo data available.Evaporation rateNo data available.Vapour densityNo data available.Decomposition temperatureNo data available.Viscosity20,000 - 30,000 mPa-sDensity0.92 - 1.01 g/ml

9.2. Other information

EU Volatile Organic CompoundsNo data available.Molecular weightNo data available.Percent volatile80.6 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Strong acids.

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Dermal Defatting: Signs/symptoms may include localised redness, itching, drying and cracking of skin.

Eve contact

Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Inhalation- Vapour		LC50 estimated to be 20 - 50 mg/l
C10-13-iso-Alkanes	Inhalation- Vapour		LC50 estimated to be 20 - 50 mg/l
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Dermal	Rabbit	LD50 > 5,000 mg/kg
C10-13-iso-Alkanes	Dermal	Rabbit	LD50 > 3,000 mg/kg
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
C10-13-iso-Alkanes	Ingestion	Rat	LD50 > 5,000 mg/kg

Calcined Kaolin	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Calcined Kaolin	Ingestion	Rat	LD50 > 2,000 mg/kg
Poly(Dimethylsiloxane)	Dermal	Rabbit	LD50 > 19,400 mg/kg
Poly(Dimethylsiloxane)	Ingestion	Rat	LD50 > 17,000 mg/kg
C10-13-iso-Alkanes	Dermal	Rabbit	LD50 > 3,160 mg/kg
C10-13-iso-Alkanes	Inhalation-	Rat	LC50 > 3 mg/l
	Dust/Mist		
	(4 hours)		
C10-13-iso-Alkanes	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminium oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium oxide	Inhalation-	Rat	LC50 > 2.3 mg/l
	Dust/Mist		
	(4 hours)		
Aluminium oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Heavy Alkylate Naphtha (Petroleum)	Dermal	Rat	LD50 > 3,000 mg/kg
Heavy Alkylate Naphtha (Petroleum)	Inhalation-	Rat	LC50 > 9.3 mg/l
	Vapour (4		
	hours)		
Heavy Alkylate Naphtha (Petroleum)	Ingestion	Rat	LD50 > 7,500 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-	Rat	LC50 > 6.82 mg/l
	Dust/Mist		
	(4 hours)		
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-	Dermal	Rabbit	LD50 87 mg/kg
2H-isothiazol-3-one			
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-	Inhalation-	Rat	LC50 0.33 mg/l
2H-isothiazol-3-one	Dust/Mist		
	(4 hours)	_	
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-	Ingestion	Rat	LD50 40 mg/kg
2H-isothiazol-3-one		1	

 \overline{ATE} = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Rabbit	Minimal irritation
C10-13-iso-Alkanes	Rabbit	Irritant
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
C10-13-iso-Alkanes	Rabbit	Mild irritant
Aluminium oxide	Rabbit	No significant irritation
Heavy Alkylate Naphtha (Petroleum)	Rabbit	Minimal irritation
Titanium dioxide	Rabbit	No significant irritation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-	Rabbit	Corrosive
one		

Serious Eye Damage/Irritation

Name	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Rabbit	Mild irritant
C10-13-iso-Alkanes	Rabbit	No significant irritation
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
C10-13-iso-Alkanes	Rabbit	Mild irritant
Aluminium oxide	Rabbit	No significant irritation
Heavy Alkylate Naphtha (Petroleum)	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-	Rabbit	Corrosive
one		

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Guinea	Not classified

	pig	
C10-13-iso-Alkanes	Guinea	Not classified
	pig	
C10-13-iso-Alkanes	Guinea	Not classified
	pig	
Heavy Alkylate Naphtha (Petroleum)	Guinea	Not classified
	pig	
Titanium dioxide	Human	Not classified
	and	
	animal	
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-	Human	Sensitising
one	and	
	animal	

Photosensitisation

Name	Species	Value
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-	Human	Not sensitising
one	and	
	animal	

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	In vivo	Not mutagenic
C10-13-iso-Alkanes	In vivo	Not mutagenic
C10-13-iso-Alkanes	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
C10-13-iso-Alkanes	In Vitro	Not mutagenic
Aluminium oxide	In Vitro	Not mutagenic
Heavy Alkylate Naphtha (Petroleum)	In Vitro	Not mutagenic
Heavy Alkylate Naphtha (Petroleum)	In vivo	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-	In vivo	Not mutagenic
one		
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-	In Vitro	Some positive data exist, but the data are not
one		sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not available	Not carcinogenic
C10-13-iso-Alkanes	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
C10-13-iso-Alkanes	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
C10-13-iso-Alkanes	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Aluminium oxide	Inhalation	Rat	Not carcinogenic
Heavy Alkylate Naphtha (Petroleum)	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	Dermal	Mouse	Not carcinogenic
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-	Ingestion	Rat	Not carcinogenic

D 0 C 10

2H-isothiazol-3-one		

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for female reproduction	Not available	NOAEL NA	1 generation
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for male reproduction	Not available	NOAEL NA	28 days
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Not specified.	Not classified for development	Not available	NOAEL NA	during gestation
C10-13-iso-Alkanes	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis
Heavy Alkylate Naphtha (Petroleum)	Inhalation	Not classified for development	Rat	NOAEL 900 ppm	during organogenesis
Mixture of 5-chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2H- isothiazol-3-one	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Mixture of 5-chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2H- isothiazol-3-one	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
Mixture of 5-chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2H- isothiazol-3-one	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Route Target Organ(s) Value Spo		Species	Test result	Exposure Duration
C10-13-iso-Alkanes	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
C10-13-iso-Alkanes	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
C10-13-iso-Alkanes	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
C10-13-iso-Alkanes	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
C10-13-iso-Alkanes	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
C10-13-iso-Alkanes	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
C10-13-iso-Alkanes	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Heavy Alkylate Naphtha (Petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Not available	NOAEL Not available	
Heavy Alkylate Naphtha (Petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	
Heavy Alkylate Naphtha (Petroleum)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Not available	NOAEL Not available	
Mixture of 5-chloro-2- methyl-2H-isothiazol-3- one and 2-methyl-2H- isothiazol-3-one	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

D 10 0 10

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
C10-13-iso-Alkanes	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
C10-13-iso-Alkanes	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
C10-13-iso-Alkanes	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
C10-13-iso-Alkanes	Inhalation	bone, teeth, nails, and/or hair blood liver muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
C10-13-iso-Alkanes	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
Aluminium oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Heavy Alkylate Naphtha (Petroleum)	Dermal	bone marrow	Not classified	Rat	NOAEL 2,000 mg/kg/day	4 weeks
Heavy Alkylate Naphtha (Petroleum)	Dermal	hematopoietic system	Not classified	Rat	NOAEL 2,000 mg/kg	4 weeks
Heavy Alkylate Naphtha (Petroleum)	Inhalation	hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 10.2 mg/l	13 weeks
Heavy Alkylate Naphtha (Petroleum)	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	4 weeks
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

Name	Value
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	Aspiration hazard
C10-13-iso-Alkanes	Aspiration hazard
C10-13-iso-Alkanes	Aspiration hazard
Heavy Alkylate Naphtha (Petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
Hydrocarbons, C11-	920-901-0	Rainbow trout	Estimated	96 hours	Lethal Level 50%	>1,000 mg/l
C13, isoalkanes, <2%						

aromatics						
Hydrocarbons, C11- C13, isoalkanes, <2% aromatics	920-901-0	Green Algae	Estimated	72 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C11- C13, isoalkanes, <2% aromatics	920-901-0	Water flea	Estimated	48 hours	Effect Level 50%	>1,000 mg/l
Hydrocarbons, C11- C13, isoalkanes, <2% aromatics	920-901-0	Green Algae	Estimated	72 hours	No obs Effect Level	1,000 mg/l
C10-13-iso-Alkanes	64742-48-9	Green Algae	Estimated	72 hours	Effect Level 50%	3.1 mg/l
C10-13-iso-Alkanes	64742-48-9	Fathead minnow	Estimated	96 hours	Lethal Level 50%	8.2 mg/l
C10-13-iso-Alkanes	64742-48-9	Water flea	Estimated	48 hours	Effect Level 50%	4.5 mg/l
C10-13-iso-Alkanes	64742-48-9	Green Algae	Estimated	72 hours	No obs Effect Level	0.5 mg/l
C10-13-iso-Alkanes	64742-48-9	Water flea	Estimated	21 days	No obs Effect Level	2.6 mg/l
Calcined Kaolin	92704-41-1	Green algae	Estimated	72 hours	EC50	2,500 mg/l
Calcined Kaolin	92704-41-1	Water flea	Estimated	48 hours	EC50	>100 mg/l
Calcined Kaolin	92704-41-1	Zebra Fish	Estimated	96 hours	LC50	>100 mg/l
Calcined Kaolin	92704-41-1	Rainbow trout	Estimated	30 days	NOEC	>100 mg/l
Calcined Kaolin	92704-41-1	Green algae	Estimated	72 hours	Effect Concentration 10%	41 mg/l
C10-13-iso-Alkanes	64742-47-8	Green Algae	Estimated	72 hours	EC50	1 mg/l
C10-13-iso-Alkanes	64742-47-8	Rainbow trout	Estimated	96 hours	Lethal Level 50%	2 mg/l
C10-13-iso-Alkanes	64742-47-8	Water flea	Estimated	48 hours	Effect Level 50%	1.4 mg/l
C10-13-iso-Alkanes	64742-47-8	Green Algae	Estimated	72 hours	No obs Effect Level	1 mg/l
C10-13-iso-Alkanes	64742-47-8	Water flea	Estimated	21 days	No obs Effect Level	0.48 mg/l
Poly(Dimethylsiloxane)	63148-62-9		Data not available or insufficient for classification		Level .	
Aluminium oxide	1344-28-1	Green Algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium oxide	1344-28-1	Green Algae	Experimental	72 hours	NOEC	>100 mg/l
Silicic acid, sodium salt, reaction products with chlorotrimethylsilane and iso-Pr alc	68988-56-7		Data not available or insufficient for classification			
Heavy Alkylate Naphtha (Petroleum)	64741-65-7		Data not available or insufficient for classification			
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l

Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
Mixture of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one	55965-84-9	Water flea	Experimental	48 hours	EC50	0.18 mg/l
Mixture of 5-chloro-2- methyl-2H-isothiazol- 3-one and 2-methyl- 2H-isothiazol-3-one	55965-84-9	Diatom	Experimental	72 hours	EC50	0.021 mg/l
Mixture of 5-chloro-2- methyl-2H-isothiazol- 3-one and 2-methyl- 2H-isothiazol-3-one	55965-84-9	Diatom	Experimental	72 hours	NOEC	0.01 mg/l

12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C11-C13,	920-901-0	Estimated	28 days	BOD	31.3 %	OECD 301F - Manometric
isoalkanes, <2% aromatics		Biodegradation			BOD/ThBOD	respirometry
C10-13-iso-Alkanes	64742-48-9	Estimated	28 days	BOD	10 %	OECD 301D - Closed bottle
		Biodegradation			BOD/ThBOD	test
Calcined Kaolin	92704-41-1	Data not availbl-			N/A	
		insufficient				
C10-13-iso-Alkanes	64742-47-8	Data not availbl-			N/A	
		insufficient				
Poly(Dimethylsiloxane)	63148-62-9	Data not availbl-			N/A	
		insufficient				
Aluminium oxide	1344-28-1	Data not availbl-			N/A	
		insufficient				
Silicic acid, sodium salt,	68988-56-7	Data not availbl-			N/A	
reaction products with		insufficient				
chlorotrimethylsilane and						
iso-Pr alc						
Heavy Alkylate Naphtha	64741-65-7	Estimated		Photolytic half-life	<4.01 days (t	Other methods
(Petroleum)		Photolysis		(in air)	1/2)	
Heavy Alkylate Naphtha	64741-65-7	Experimental	28 days	BOD	8-22 % weight	OECD 301D - Closed bottle
(Petroleum)		Biodegradation				test
Titanium dioxide	13463-67-7	Data not availbl-			N/A	
		insufficient				
Mixture of 5-chloro-2-	55965-84-9	Data not availbl-			N/A	
methyl-2H-isothiazol-3-one		insufficient				
and 2-methyl-2H-isothiazol-						
3-one						

12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	920-901-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
C10-13-iso-Alkanes	64742-48-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Calcined Kaolin	92704-41-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
C10-13-iso-Alkanes	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Poly(Dimethylsiloxane)	63148-62-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Aluminium oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

Silicic acid, sodium salt, reaction products with chlorotrimethylsilane and iso-Pr alc	68988-56-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Heavy Alkylate Naphtha (Petroleum)	64741-65-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF- Carp	42 days	Bioaccumulation factor	9.6	Other methods
Mixture of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H- isothiazol-3-one	55965-84-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

See Section 11.1 Information on toxicological effects

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

EU waste code (product as sold)

120120* Spent grinding bodies and grinding materials containing dangerous substances

SECTION 14: Transportation information

ADR/IMDG/IATA: Not restricted for transport.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	Regulation
Titanium dioxide	13463-67-7	Grp. 2B: Possible human	International Agency
		carc.	for Research on Cancer

Global inventory status

Contact manufacturer for more information The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision information:

- Label: CLP Classification information was deleted.
- Label: CLP Classification information was modified.
- Label: CLP Precautionary General information was deleted.
- Label: CLP Precautionary Response information was deleted.
- Label: Graphic information was deleted.
- Label: Signal Word information was deleted.
- Section 3: Composition/Information of ingredients table information was modified.
- Section 4: First aid for skin contact information information was modified.
- Section 7: Precautions safe handling information information was modified.
- Section 8: glove data value information was modified.
- Section 8: Occupational exposure limit table information was modified.
- Section 8: Personal Protection Skin/hand information information was modified.
- Section 9: Flash point information information was modified.
- Section 11: Acute Toxicity table information was modified.
- Section 11: Aspiration Hazard Table information was modified.
- Section 11: Cancer Hazards information information was added.
- Section 11: Carcinogenicity Table information was modified.
- Section 11: Germ Cell Mutagenicity Table information was modified.
- Section 11: Health Effects Ingestion information information was modified.
- Section 11: Health Effects Inhalation information information was modified.
- Section 11: Health Effects Skin information information was modified.
- Section 11: Reproductive Toxicity Table information was modified.
- Section 11: Serious Eye Damage/Irritation Table information was modified.

D166, Ultra Polishing Wax (26-123A): D16616, D16601

- Section 11: Skin Corrosion/Irritation Table information was modified.
- Section 11: Skin Sensitization Table information was modified.
- Section 11: Target Organs Repeated Table information was modified.
- Section 11: Target Organs Single Table information was modified.
- Section 12: Component ecotoxicity information information was modified.
- Section 12: No PBT/vPvB information available warning information was modified.
- Section 12: Persistence and Degradability information information was modified.
- Section 12:Bioccumulative potential information information was modified.
- Section 15: Carcinogenicity information information was added.
- Section 15: Chemical Safety Assessment information was modified.
- Section 15: Label remarks and EU Detergent information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

Section 16: Web address information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Meguiar's, Inc. United Kingdom SDSs are available at www.meguiars.co.uk