

# Safety Data Sheet

Copyright,2023, Meguiar's Inc. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Meguiar's Inc. products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Meguiar's Inc., and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 39-4712-4 **Version number:** 3.01

**Revision date:** 07/11/2023 **Supersedes date:** 16/12/2022

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

# **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

#### 1.1. Product identifier

Deep Crystal™ Ceramic Coating M788 [M78802]

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### **Identified uses**

Automotive.

#### 1.3. Details of the supplier of the safety data sheet

Address: Meguiars United Kingdom Limited, 3 Lamport Court, Heartlands, Daventry, Northants, NN11 8UF

Telephone: +44 (0)870 241 6696 E Mail: info@meguiars.co.uk Website: www.meguiars.co.uk

#### 1.4. Emergency telephone number

+44 (0)870 241 6696

# **SECTION 2: Hazard identification**

#### 2.1. Classification of the substance or mixture

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

#### **CLASSIFICATION:**

Flammable Liquid, Category 2 - Flam. Liq. 2; H225

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

Aspiration Hazard, Category 1 - Asp. Tox. 1; H304

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

#### 2.2. Label elements

The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

#### SIGNAL WORD

DANGER.

## **Symbols**

GHS02 (Flame) |GHS07 (Exclamation mark) |GHS08 (Health Hazard) |

#### **Pictograms**







Ingredient	CAS Nbr	EC No.	% by Wt
acetone	67-64-1	200-662-2	10 - 30
Mineral oil	8042-47-5	232-455-8	10 - 30
stoddard solvent	8052-41-3	232-489-3	< 10
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)		919-446-0	1 - 5

#### **HAZARD STATEMENTS:**

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H373 May cause damage to organs through prolonged or repeated exposure: nervous system.

H412 Harmful to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

**Prevention:** 

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260G Do not breathe vapours or dust.

**Response:** 

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or

carbon dioxide to extinguish.

#### SUPPLEMENTAL INFORMATION:

# **Supplemental Hazard Statements:**

**EUH066** 

Repeated exposure may cause skin dryness or cracking.

7% of the mixture consists of components of unknown acute oral toxicity.

Contains 4% of components with unknown hazards to the aquatic environment.

Nota P applied.

#### 2.3. Other hazards

Contains a substance that meets the criteria for PBT according to Regulation (EC) No 1907/2006, Annex XIII, as amended by UK REACH Regulations SI 2019/758 Contains a substance that meets the criteria for vPvB according to Regulation (EC) No 1907/2006, Annex XIII, as amended by UK REACH Regulations SI 2019/758

# **SECTION 3: Composition/information on ingredients**

## 3.1. Substances

Not applicable

#### 3.2. Mixtures

Ingredient	Identifier(s)	9/0	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Polysiloxane with Functionalized Silica	Trade Secret	15 - 40	Substance not classified as hazardous
Mineral oil	(CAS-No.) 8042-47-5 (EC-No.) 232-455-8	10 - 30	Asp. Tox. 1, H304
acetone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2	10 - 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066
stoddard solvent	(CAS-No.) 8052-41-3 (EC-No.) 232-489-3	< 10	Asp. Tox. 1, H304 STOT RE 1, H372 Nota P Skin Irrit. 2, H315 Aquatic Chronic 3, H412
Propoxypropanol	(CAS-No.) 1569-01-3 (EC-No.) 216-372-4	3 - 7	Flam. Liq. 3, H226 Eye Irrit. 2, H319
Acrylic Polymer	Trade Secret	1 - 5	Substance not classified as hazardous
Functionalized Silica	Trade Secret	1 - 5	Substance not classified as hazardous
2-methoxy-1-methylethyl acetate	(CAS-No.) 108-65-6 (EC-No.) 203-603-9	1 - 5	Flam. Liq. 3, H226 STOT SE 3, H336
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	(EC-No.) 919-446-0	1 - 5	Aquatic Chronic 2, H411 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH066 STOT RE 1, H372
Silicone Resin Blend	Trade Secret	1 - 3	Substance not classified as hazardous

ethylbenzene	(CAS-No.) 100-41-4	< 0.5	Flam. Liq. 2, H225
	(EC-No.) 202-849-4		Acute Tox. 4, H332
			Asp. Tox. 1, H304
			STOT RE 2, H373
			Aquatic Chronic 3, H412
NONANE	(CAS-No.) 111-84-2	< 0.5	Aquatic Acute 1, H400,M=1
	(EC-No.) 203-913-4		Aquatic Chronic 1, H410,M=1
			Flam. Liq. 3, H226
			Acute Tox. 4, H332
			Asp. Tox. 1, H304
			STOT SE 3, H336
octamethylcyclotetrasiloxane	(CAS-No.) 556-67-2	< 0.1	Repr. 2, H361f
	(EC-No.) 209-136-7		Aquatic Chronic 1, H410,M=10
			Flam. Liq. 3, H226

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eve contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If swallowed

Do not induce vomiting. Get immediate medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the GB CLP classification include:

Toxic by eye contact. Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Aspiration pneumonitis (coughing, gasping, choking, burning of the mouth, and difficulty breathing). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

# 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

# **SECTION 5: Fire-fighting measures**

#### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

#### 5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

#### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

#### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

## 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

#### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component

Ingredient	CAS Nbr	Agency	Limit type	<b>Additional comments</b>
ethylbenzene	100-41-4	UK HSC	TWA:441 mg/m3(100 ppm);STEL:552 mg/m3(125 ppm)	SKIN
2-methoxy-1-methylethyl acetate	108-65-6	UK HSC	TWA:274 mg/m3(50 ppm);STEL:548 mg/m3(100 ppm)	SKIN
acetone	67-64-1	UK HSC	TWA:1210 mg/m³(500 ppm);STEL:3620 mg/m³(1500 ppm)	

UK HSC: UK Health and Safety Commission

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

# **Biological limit values**

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

Applicable Norms/Standards

Use eye protection conforming to EN 166

## Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	>.3	=>8 hours
Polyvinyl alcohol (PVA).	>.3	4-8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

#### Deep Crystal<sup>TM</sup> Ceramic Coating M788 [M78802]

Applicable Norms/Standards Use gloves tested to EN 374

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates Organic vapour respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state Liquid.

Colour Pale White, Transparent Colorless
Odor Characteristic Odour

Odor Characteristic Odour Odour threshold No data available.

Melting point/freezing pointNo data available.Boiling point/boiling range60 °C

Flammability (solid, gas)

Flammable Limits(LEL)

No data available.

Flammable Limits(UEL)

No data available.

Flash point -1.5 °C [Test Method:Closed Cup]

25 mm<sup>2</sup>/sec

**Autoignition temperature**No data available. **Decomposition temperature**No data available.

рН

Water solubility
No data available.
Solubility- non-water
No data available.
Partition coefficient: n-octanol/water
No data available.

Vapour pressure

No data available.

No data available.

No data available.

0.8988 g/ml

Relative density 0.8988 [Ref Std:WATER=1]

**Relative Vapour Density** *No data available.* 

#### 9.2. Other information

**Kinematic Viscosity** 

9.2.2 Other safety characteristics

Average particle size

Bulk density

No data available.

EU Volatile Organic Compounds

Evaporation rate

Molecular weight

Percent volatile

Softening point

No data available.

\_\_\_\_\_

<sup>\*</sup> The values noted with an asterisk (\*) in the above table are representative values based on testing of raw materials and selected products. Additionally, a material's characteristics may change depending upon the process and conditions of use at

a facility, including further changes in particle size, or mixture with other materials. In order to obtain specific data for the material, we recommend the user conduct characterisation testing based on the use factors at the specific facility.

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

#### 10.2 Chemical stability

Stable.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.4 Conditions to avoid

Sparks and/or flames.

#### 10.5 Incompatible materials

Strong oxidising agents.

# 10.6 Hazardous decomposition products

**Substance** 

Condition

None known.

# **SECTION 11: Toxicological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

#### Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### Ingestion

Chemical (aspiration) pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish coloured skin (cyanosis), and may be fatal. Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

#### **Additional Health Effects:**

### Single exposure may cause target organ effects:

Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

## Prolonged or repeated exposure may cause target organ effects:

Central neuropathy: Signs/symptoms may include irritability, memory impairment, personality changes, sleep disorders, and decreased ability to concentrate.

## Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polysiloxane with Functionalized Silica	Dermal	Rabbit	LD50 > 19,400 mg/kg
Polysiloxane with Functionalized Silica	Ingestion	Rat	LD50 > 17,000 mg/kg
acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
acetone	Inhalation- Vapour (4 hours)	Rat	LC50 76 mg/l
acetone	Ingestion	Rat	LD50 5,800 mg/kg
Mineral oil	Dermal	Rabbit	LD50 > 2,000 mg/kg
Mineral oil	Ingestion	Rat	LD50 > 5,000 mg/kg
Propoxypropanol	Dermal	Rabbit	LD50 2,805 mg/kg
Propoxypropanol	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 11.8 mg/l
Propoxypropanol	Ingestion	Rat	LD50 2,500 mg/kg
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Dermal	Rat	LD50 > 3,400 mg/kg
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Inhalation- Vapour (4 hours)	Rat	LC50 > 16.2 mg/l
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Ingestion	Rat	LD50 > 15,000 mg/kg
stoddard solvent	Inhalation- Vapour		LC50 estimated to be 20 - 50 mg/l
stoddard solvent	Dermal	Rabbit	LD50 > 3,000 mg/kg
stoddard solvent	Ingestion	Rat	LD50 > 5,000 mg/kg
2-methoxy-1-methylethyl acetate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-methoxy-1-methylethyl acetate	Inhalation- Vapour (4 hours)	Rat	LC50 > 28.8 mg/l
2-methoxy-1-methylethyl acetate	Ingestion	Rat	LD50 8,532 mg/kg
NONANE	Inhalation- Vapour (4 hours)	Rat	LC50 17 mg/l
NONANE	Dermal	similar compoun ds	LD50 > 2,000 mg/kg
NONANE	Ingestion	similar compoun ds	LD50 > 5,000 mg/kg

# Deep Crystal™ Ceramic Coating M788 [M78802]

ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
ethylbenzene	Inhalation-	Rat	LC50 17.4 mg/l
	Vapour (4		
	hours)		
ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
octamethylcyclotetrasiloxane	Dermal	Rat	LD50 > 2,400 mg/kg
octamethylcyclotetrasiloxane	Inhalation-	Rat	LC50 36 mg/l
	Dust/Mist		
	(4 hours)		
octamethylcyclotetrasiloxane	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

Name	Species	Value
Polysiloxane with Functionalized Silica	Rabbit	No significant irritation
acetone	Mouse	Minimal irritation
Mineral oil	Rabbit	No significant irritation
Propoxypropanol	Rabbit	Minimal irritation
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Rabbit	Minimal irritation
stoddard solvent	Rabbit	Irritant
2-methoxy-1-methylethyl acetate	Rabbit	No significant irritation
NONANE	similar	No significant irritation
	compoun	
	ds	
ethylbenzene	Rabbit	Mild irritant
octamethylcyclotetrasiloxane	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Polysiloxane with Functionalized Silica	Rabbit	No significant irritation
acetone	Rabbit	Severe irritant
Mineral oil	Rabbit	Mild irritant
Propoxypropanol	Rabbit	Severe irritant
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Rabbit	No significant irritation
stoddard solvent	Rabbit	No significant irritation
2-methoxy-1-methylethyl acetate	Rabbit	Mild irritant
NONANE	similar	Mild irritant
	compoun	
	ds	
ethylbenzene	Rabbit	Moderate irritant
octamethylcyclotetrasiloxane	Rabbit	No significant irritation

#### **Skin Sensitisation**

Name	Species	Value
Mineral oil	Guinea pig	Not classified
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Guinea pig	Not classified
stoddard solvent	Guinea pig	Not classified
2-methoxy-1-methylethyl acetate	Guinea pig	Not classified
NONANE	similar compoun ds	Not classified
ethylbenzene	Human	Not classified
octamethylcyclotetrasiloxane	Human and animal	Not classified

# **Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
acetone	In vivo	Not mutagenic
acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Mineral oil	In Vitro	Not mutagenic
Propoxypropanol	In Vitro	Not mutagenic
stoddard solvent	In vivo	Not mutagenic
stoddard solvent	In Vitro	Some positive data exist, but the data are not sufficient for classification
2-methoxy-1-methylethyl acetate	In Vitro	Not mutagenic
NONANE	In Vitro	Not mutagenic
ethylbenzene	In vivo	Not mutagenic
ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
octamethylcyclotetrasiloxane	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
acetone	Not	Multiple	Not carcinogenic
	specified.	animal	-
		species	
Mineral oil	Dermal	Mouse	Not carcinogenic
Mineral oil	Inhalation	Multiple	Not carcinogenic
		animal	
		species	
stoddard solvent	Dermal	Mouse	Some positive data exist, but the data are not
			sufficient for classification
stoddard solvent	Inhalation	Human	Some positive data exist, but the data are not
		and	sufficient for classification
		animal	
ethylbenzene	Inhalation	Multiple	Carcinogenic.
		animal	
		species	

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
Mineral oil	Ingestion	Not classified for female reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral oil	Ingestion	Not classified for male reproduction	Rat	NOAEL 4,350 mg/kg/day	13 weeks
Mineral oil	Ingestion	Not classified for development	Rat	NOAEL 4,350 mg/kg/day	during gestation
Propoxypropanol	Inhalation	Not classified for development	Rat	NOAEL 3.6 mg/l	during organogenesis
stoddard solvent	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis
2-methoxy-1-methylethyl acetate	Ingestion	Not classified for female reproduction	Rat	NOAEL	premating &

Dogge 11 of 2

				1,000 mg/kg/day	during gestation
2-methoxy-1-methylethyl acetate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
2-methoxy-1-methylethyl acetate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
2-methoxy-1-methylethyl acetate	Inhalation	Not classified for development	Rat	NOAEL 21.6 mg/l	during organogenesis
ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	premating & during gestation
octamethylcyclotetrasiloxane	Inhalation	Not classified for male reproduction	Rat	NOAEL 8.5 mg/l	2 generation
octamethylcyclotetrasiloxane	Ingestion	Toxic to female reproduction	Rabbit	NOAEL 50 mg/kg/day	during organogenesis
octamethylcyclotetrasiloxane	Inhalation	Toxic to female reproduction	Rat	NOAEL 3.6 mg/l	2 generation

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name Route Target Organ(s) Value		Value	Species	Test result	Exposure Duration	
acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Propoxypropanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	LOAEL 10.8 mg/l	6 hours
Propoxypropanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Propoxypropanol	ypropanol Ingestion central nervous system depression dizziness Rat		Rat	LOAEL 1,770 mg/kg	not applicable	
Hydrocarbons C9-12 N- alkanes, isoalkanes cyclic aromatics (2-25%)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	similar compoun ds	NOAEL not available	
Hydrocarbons C9-12 N- alkanes, isoalkanes cyclic aromatics (2-25%)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	similar compoun ds	NOAEL not available	
stoddard solvent	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
stoddard solvent	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
stoddard solvent	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
stoddard solvent	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
2-methoxy-1-methylethyl acetate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
2-methoxy-1-methylethyl acetate	Ingestion	central nervous system depression	Some positive data exist, but the data are not sufficient for	Rat	NOAEL not available	

			classification		
NONANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available
NONANE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available
ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available
ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available
ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
acetone	Inhalation	heart   liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
acetone	Ingestion	skin   bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Mineral oil	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,381 mg/kg/day	90 days
Mineral oil	Ingestion	liver   immune system	Not classified	Rat	NOAEL 1,336 mg/kg/day	90 days
Propoxypropanol	Inhalation	liver   kidney and/or bladder	Not classified	Rat	NOAEL 9.5 mg/l	11 days
Hydrocarbons C9-12 N- alkanes, isoalkanes cyclic aromatics (2-25%)	Inhalation	central nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL not available	occupational exposure
stoddard solvent	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
stoddard solvent	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
stoddard solvent	Inhalation	respiratory system	Not classified	Multiple	NOAEL 0.6	90 days

\_\_\_\_\_

				animal species	mg/l	
stoddard solvent	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
stoddard solvent	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
2-methoxy-1-methylethyl acetate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 16.2 mg/l	9 days
2-methoxy-1-methylethyl acetate	Inhalation	olfactory system	Not classified	Mouse	LOAEL 1.62 mg/l	9 days
2-methoxy-1-methylethyl acetate	Inhalation	blood	Not classified	Multiple animal species	NOAEL 16.2 mg/l	9 days
2-methoxy-1-methylethyl acetate	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	44 days
NONANE	Inhalation	nervous system   heart   endocrine system   gastrointestinal tract   hematopoietic system   liver   muscles   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 8.4 mg/l	90 days
NONANE	Ingestion	endocrine system   gastrointestinal tract   hematopoietic system   liver   respiratory system   heart   bone, teeth, nails, and/or hair   immune system   nervous system   kidney and/or bladder   vascular system	Not classified	Rat	NOAEL 5,000 mg/kg/day	90 days
ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
ethylbenzene	Inhalation	bone, teeth, nails, and/or hair   muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
ethylbenzene	Inhalation	heart   immune system   respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
ethylbenzene	Ingestion	liver   kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
octamethylcyclotetrasiloxa ne	Dermal	hematopoietic system	Not classified	Rabbit	NOAEL 960 mg/kg/day	3 weeks
octamethylcyclotetrasiloxa ne	Inhalation	liver	Not classified	Rat	NOAEL 8.5 mg/l	13 weeks
octamethylcyclotetrasiloxa ne	Inhalation	endocrine system   immune system   kidney and/or	Not classified	Rat	NOAEL 8.5 mg/l	2 generation

		bladder				
octamethylcyclotetrasiloxa	Inhalation	hematopoietic	Not classified	Rat	NOAEL 8.5	13 weeks
ne		system			mg/l	
octamethylcyclotetrasiloxa	Ingestion	liver	Not classified	Rat	NOAEL	2 weeks
ne					1,600	
					mg/kg/day	

**Aspiration Hazard** 

Name	Value
Mineral oil	Aspiration hazard
Hydrocarbons C9-12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	Aspiration hazard
stoddard solvent	Aspiration hazard
NONANE	Aspiration hazard
ethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

#### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

# **SECTION 12: Ecological information**

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

#### 12.1. Toxicity

No product test data available.

Material	CAS#	Organism	Type	Exposure	Test endpoint	Test result
Polysiloxane with Functionalized Silica	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
acetone	67-64-1	Algae or other aquatic plants	Experimental	96 hours	EC50	11,493 mg/l
acetone	67-64-1	Invertebrate	Experimental	24 hours	LC50	2,100 mg/l
acetone	67-64-1	Rainbow trout	Experimental	96 hours	LC50	5,540 mg/l
acetone	67-64-1	Water flea	Experimental	21 days	NOEC	1,000 mg/l
acetone	67-64-1	Bacteria	Experimental	16 hours	NOEC	1,700 mg/l
acetone	67-64-1	Redworm	Experimental	48 hours	LC50	>100
Mineral oil	8042-47-5	Water flea	Analogous Compound	48 hours	EL50	>100 mg/l
Mineral oil	8042-47-5	Bluegill	Experimental	96 hours	LL50	>100 mg/l
Mineral oil	8042-47-5	Green algae	Analogous Compound	72 hours	NOEL	100 mg/l
Mineral oil	8042-47-5	Water flea	Analogous Compound	21 days	NOEL	>100 mg/l
stoddard solvent	8052-41-3	Green algae	Estimated	96 hours	EL50	2.5 mg/l
stoddard solvent	8052-41-3	Invertebrate	Estimated	96 hours	LC50	3.5 mg/l
stoddard solvent	8052-41-3	Rainbow trout	Estimated	96 hours	LL50	41.4 mg/l

stoddard solvent	8052-41-3	Green algae	Estimated	96 hours	NOEL	0.76 mg/l
stoddard solvent	8052-41-3	Green algae	Estimated	96 nours	NOEL	0.76 mg/1
stoddard solvent	8052-41-3	Water flea	Estimated	21 days	NOEC	0.28 mg/l
Propoxypropanol	1569-01-3	Green algae	Experimental	96 hours	EC50	1,466 mg/l
Propoxypropanol	1569-01-3	Rainbow trout	Experimental	96 hours	LC50	>100 mg/l
Propoxypropanol	1569-01-3	Water flea	Experimental	48 hours	LC50	>100 mg/l
2-methoxy-1- methylethyl acetate	108-65-6	Activated sludge	Experimental	30 minutes	EC10	>1,000 mg/l
2-methoxy-1- methylethyl acetate	108-65-6	Green algae	Experimental	72 hours	ErC50	>1,000 mg/l
2-methoxy-1- methylethyl acetate	108-65-6	Rainbow trout	Experimental	96 hours	LC50	134 mg/l
2-methoxy-1- methylethyl acetate	108-65-6	Water flea	Experimental	48 hours	EC50	370 mg/l
2-methoxy-1- methylethyl acetate	108-65-6	Green algae	Experimental	72 hours	NOEC	1,000 mg/l
2-methoxy-1- methylethyl acetate	108-65-6	Water flea	Experimental	21 days	NOEC	100 mg/l
Functionalized Silica	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Hydrocarbons C9- 12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Green algae	Experimental	72 hours	EL50	4.1 mg/l
Hydrocarbons C9- 12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Rainbow trout	Experimental	96 hours	LL50	30 mg/l
Hydrocarbons C9- 12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Water flea	Experimental	48 hours	EL50	22 mg/l
Hydrocarbons C9- 12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Green algae	Experimental	72 hours	NOEL	0.76 mg/l
Hydrocarbons C9- 12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Water flea	Experimental	21 days	EL10	0.316 mg/l
ethylbenzene	100-41-4	Activated sludge	Experimental	49 hours	EC50	130 mg/l
ethylbenzene	100-41-4	Atlantic Silverside	Experimental	96 hours	LC50	5.1 mg/l
ethylbenzene	100-41-4	Green algae	Experimental	96 hours	EC50	3.6 mg/l
ethylbenzene	100-41-4	Mysid Shrimp	Experimental	96 hours	LC50	2.6 mg/l
ethylbenzene	100-41-4	Rainbow trout	Experimental	96 hours	LC50	4.2 mg/l
ethylbenzene	100-41-4	Water flea	Experimental	48 hours	EC50	1.8 mg/l
ethylbenzene	100-41-4	Water flea	Experimental	7 days	NOEC	0.96 mg/l
NONANE	111-84-2	Water flea	Experimental	48 hours	EC50	0.2 mg/l
octamethylcyclotetr asiloxane	556-67-2	Blackworm	Experimental	28 days	NOEC	0.73 mg/kg (Dry Weight)
octamethylcyclotetr asiloxane	556-67-2	Midge	Experimental	14 days	LC50	>170 mg/kg (Dry Weight)
octamethylcyclotetr asiloxane	556-67-2	Mysid Shrimp	Experimental	96 hours	LC50	>0.0091 mg/l

octamethylcyclotetr asiloxane	556-67-2	Rainbow trout	Experimental	96 hours	LC50	>0.022 mg/l
octamethylcyclotetr	556-67-2	Water flea	Experimental	48 hours	EC50	>0.015 mg/l
asiloxane						
octamethylcyclotetr	556-67-2	Rainbow trout	Experimental	93 days	NOEC	0.0044 mg/l
asiloxane						
octamethylcyclotetr	556-67-2	Water flea	Experimental	21 days	NOEC	0.015 mg/l
asiloxane						
octamethylcyclotetr	556-67-2	Activated sludge	Experimental	3 hours	EC50	>10,000 mg/l
asiloxane						

# 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Polysiloxane with Functionalized Silica	Trade Secret	Data not availbl- insufficient	N/A	N/A	N/A	N/A
acetone	67-64-1	Experimental Biodegradation	28 days	BOD	78 %BOD/ThOD	OECD 301D - Closed bottle test
acetone	67-64-1	Experimental Photolysis		Photolytic half-life (in air)	147 days (t 1/2)	
Mineral oil	8042-47-5	Experimental Biodegradation	28 days	CO2 evolution	0 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
stoddard solvent	8052-41-3	Experimental Biodegradation	28 days	CO2 evolution	>63 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
stoddard solvent	8052-41-3	Experimental Photolysis		(in air)	6.49 days (t 1/2)	
Propoxypropanol	1569-01-3	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	91.5 %removal of DOC	OECD 301A - DOC Die Away Test
2-methoxy-1- methylethyl acetate	108-65-6	Experimental Biodegradation	28 days	BOD	87.2 %BOD/ThOD	OECD 301C - MITI test (I)
2-methoxy-1- methylethyl acetate	108-65-6	Experimental Aquatic Inherent Biodegrad.		Dissolv. Organic Carbon Deplet	>100 %removal of DOC	similar to OECD 302B
Functionalized Silica	Trade Secret	Data not availbl- insufficient	N/A	N/A	N/A	N/A
Hydrocarbons C9- 12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Analogous Compound Biodegradation	28 days	BOD	74.7 %BOD/ThOD	OECD 301F - Manometric respirometry
ethylbenzene	100-41-4	Experimental Biodegradation	28 days	CO2 evolution	70-80 %CO2 evolution/THCO2 evolution	ISO 14593 Inorg C Headspace
ethylbenzene	100-41-4	Experimental Photolysis		Photolytic half-life (in air)	4.26 days (t 1/2)	
NONANE	111-84-2	Experimental Biodegradation	28 days	BOD	96 %BOD/ThOD	
NONANE	111-84-2	Experimental Photolysis		Photolytic half-life (in air)	3.07 days (t 1/2)	
octamethylcyclotetr asiloxane	556-67-2	Experimental Biodegradation	29 days	CO2 evolution	3.7 %CO2 evolution/THCO2 evolution	OECD 310 CO2 Headspace
octamethylcyclotetr asiloxane		Experimental Photolysis		Photolytic half-life (in air)	31 days (t 1/2)	
octamethylcyclotetr asiloxane	556-67-2	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	69.3-144 hours (t 1/2)	OECD 111 Hydrolysis func of pH

# 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Polysiloxane with Functionalized	Trade Secret	Data not available or insufficient for	N/A	N/A	N/A	N/A
Silica		classification				

acetone	67-64-1	Experimental BCF - Other		Bioaccumulation factor	0.65	
acetone	67-64-1	Experimental Bioconcentration		Log Kow	-0.24	
Mineral oil	8042-47-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
stoddard solvent	8052-41-3	Estimated Bioconcentration		Log Kow	6.4	
Propoxypropanol	1569-01-3	Estimated Bioconcentration		Log Kow	0.62	
2-methoxy-1- methylethyl acetate	108-65-6	Experimental Bioconcentration		Log Kow	0.36	OECD 107 log Kow shke flsk mtd
Functionalized Silica	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons C9- 12 N-alkanes, isoalkanes cyclic aromatics (2-25%)	919-446-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
ethylbenzene	100-41-4	Experimental BCF - Fish	42 days	Bioaccumulation factor	1	
NONANE	111-84-2	Experimental Bioconcentration		Log Kow	5.65	
octamethylcyclotetr asiloxane	556-67-2	Experimental BCF - Fish	28 days	Bioaccumulation factor	12400	40CFR 797.1520-Fish Bioaccumm
octamethylcyclotetr asiloxane	556-67-2	Experimental Bioconcentration		Log Kow	6.49	OECD 123 log Kow slow stir

### 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
acetone	67-64-1	Modeled Mobility in Soil	Koc	9.7 l/kg	Episuite <sup>TM</sup>
Propoxypropanol	1569-01-3	Estimated Mobility in Soil	Koc	2 l/kg	Episuite <sup>TM</sup>
2-methoxy-1- methylethyl acetate	108-65-6	Experimental Mobility in Soil	Koc	4 l/kg	Episuite <sup>TM</sup>
NONANE	111-84-2	Modeled Mobility in Soil	Koc	80,000 l/kg	Episuite <sup>TM</sup>
octamethylcyclotetr asiloxane	556-67-2	Experimental Mobility in Soil	Koc	16,600 l/kg	OECD 106 Adsp-Desb Batch Equil

## 12.5. Results of the PBT and vPvB assessment

Ingredient	CAS Nbr	PBT/vPvB status
octamethylcyclotetrasiloxane	556-67-2	Meets UK REACH PBT criteria
octamethylcyclotetrasiloxane	556-67-2	Meets UK REACH vPvB criteria

#### 12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated

& disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of the manufacturer, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/CE and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor

#### EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances

# SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number	UN1139	UN1139	UN1139
14.2 UN proper shipping name	COATING SOLUTION	COATING SOLUTION	COATING SOLUTION
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	II	II	II
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Transport in bulk according to Annex II of Marpol 73/78 and IBC Code	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	F1	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

# **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	CAS Nbr	Classification	Regulation
ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

#### Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject to Annex XVII of regulation (EC) 1907/2006, as amended for GB, with regard to restrictions on the manufacture, placing on the market and use when present in certain dangerous conditions. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

IngredientCAS Nbroctamethylcyclotetrasiloxane556-67-2

Restriction status: listed in UK REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 as amended for Great Britain for Conditions of

Restriction

#### **Authorisation status under UK REACH:**

The following substance/s contained in this product might be or is/are subject to authorisation in accordance with UK REACH:

IngredientCAS Nbroctamethylcyclotetrasiloxane556-67-2

Authorisation status: listed in the UK REACH Candidate List of Substances of Very High Concern for Authorisation

#### Regulation UK regulation 2023/63 (marketing and use of explosive precursors and poisons)

This product contains a reportable substance according to UK legislation 1972/66: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see UK Regulation 2023/63 for further details.

#### Global inventory status

Contact manufacturer for more information The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### **COMAH Regulation, SI 2015/483**

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
P5c FLAMMABLE LIQUIDS*	5000	50000

\*If maintained at a temperature above its boiling point or if particular processing conditions, such as high pressure or high temperature, may create major-accident hazards, P5a or P5b FLAMMABLE LIQUIDS may apply Seveso named dangerous substances, Annex 1, Part 2

Dangerous Substances	Identifier(s)	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
		requirements	
2-methoxy-1-methylethyl	108-65-6	10	50
acetate			
acetone	67-64-1	10	50
ethylbenzene	100-41-4	10	50
octamethylcyclotetrasiloxane	556-67-2	100	200

#### Regulation (EU) No 649/2012, as amended for GB

No chemicals listed

#### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

# **SECTION 16: Other information**

#### List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### **Revision information:**

- GB Section 02: CLP Ingredient table information was added.
- GB Section 02: CLP Remark(phrase) information was added.
- GB Section 02: Other hazards phrase information was added.
- GB Section 04: First Aid Symptoms and Effects (GB CLP) information was added.
- GB Section 04: Information on toxicological effects information was added.
- GB Section 12: Classification Warning information was added.
- GB Section 12: PBT/vPvB table row information was added.
- GB Section 15: Authorisation status under REACH: SVHC Authorisation ingredient information information was added.
- GB Section 15: Carcinogenicity information information was added.
- GB Section 15: Chemical Safety Assessment information was added.
- GBSDS Section 14 Transport in bulk Main Heading information was added.

### Deep Crystal™ Ceramic Coating M788 [M78802]

GBSDS Section 14 UN Number information was added.

CLP: Ingredient table information was deleted.

CLP Remark(phrase) information was deleted.

Label: CLP Percent Unknown information was deleted.

Section 02: Label Elements: GB Percent Unknown information was added.

Section 2: Other hazards phrase information was deleted.

Section 3: Composition/Information of ingredients table information was added.

Section 3: Composition/ Information of ingredients table information was deleted.

Section 04: First Aid - Symptoms and Effects (CLP) information was deleted.

Section 04: Information on toxicological effects information was deleted.

Section 11: Acute Toxicity table information was modified.

Section 11: Aspiration Hazard Table information was modified.

Section 11: Classification disclaimer information was deleted.

Section 11: GB Classification disclaimer information was added.

Section 11: GB No endocrine disruptor information available warning information was added.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: No endocrine disruptor information available warning information was deleted.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.

Section 11: Skin Sensitization Table information was modified.

Section 11: Target Organs - Repeated Table information was modified.

Section 11: Target Organs - Single Table information was modified.

Section 12: 12.6. Endocrine Disrupting Properties information was deleted.

Section 12: 12.6. Other adverse effects information was added.

Section 12: 12.7. Other adverse effects information was deleted.

Section 12: Classification Warning information was deleted.

Section 12: Component ecotoxicity information information was modified.

Prints No Data if Adverse effects information is not present information was deleted.

Section 12: No endocrine disruptor information available warning information was added.

Section 12: No endocrine disruptor information available warning information was deleted.

Section 12: PBT/vPvB table row information was deleted.

Section 12: Persistence and Degradability information information was modified.

Section 14 Classification Code – Regulation Data information was modified.

Section 14 Hazard Class + Sub Risk – Regulation Data information was modified.

Section 14 Hazardous/Not Hazardous for Transportation information was added.

Section 14 Other Dangerous Goods – Regulation Data information was modified.

Section 14 Packing Group – Regulation Data information was modified.

Section 14 Proper Shipping Name information was modified.

Section 14 Segregation – Regulation Data information was modified.

Section 14 Marine transport in bulk according to IMO instruments - Main Heading information was deleted.

Section 14 UN Number Column data information was modified.

Section 14 UN Number information was deleted.

Section 14: Transportation classification information was deleted.

Section 15: Authorization status under REACH: SVHC Authorization ingredient information information was deleted.

Section 15: Carcinogenicity information information was deleted.

Section 15: Chemical Safety Assessment information was deleted.

Section 15: Seveso Hazard Category Text information was added.

Section 15: Seveso Hazard Category Text information was deleted.

Section 15: Seveso Substance Text information was added.

Section 15: Seveso Substance Text information was deleted.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was added.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was deleted.

Section 16: Web address information was added.

Section 16: Web address information was deleted.

#### Deep Crystal™ Ceramic Coating M788 [M78802]

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

# Meguiar's, Inc. SDSs for Great Britain are available at www.meguiars.co.uk

For Northern Ireland documents, please contact your 3M representative to obtain a copy.